

Data Sheet

DS-4016	Issue Date	
D3-4010	00/13/17	11/12/21

Waterous Traditional CAFS

As used with CM and CS Series Fire Pumps

Available as follows:

	CAFS		Pump and Transmission			
Drive	Model (Air	Water (U.S. GPM)	Pump		Transmission Model
		(CFM)		Model	Material	Transmission Model
Belt off Back of Pump Transmission	150-D	150	300	CM, CMU, CS, CSU	Iron	C20B, C20C, C20D, C20E, C20F
(Direct Drive)				CM, CS (CMU and CSU Not Available)	Iron	PA
Belt off Back of Pump Transmission (Via a Pneumatic Clutch)	Eclipse	200	400	CMU (CM Not Available) CS, CSU	Iron	C20B, C20C, C20D, C20E, C20F

Specify a CAF System as follows:

Voltage:

12 or 24

Model:

150-D or Eclipse

Sump:

Model 150-D:

Vertical (Shipped Loose)

Tee (Optional)

Model Eclipse:

Encapsulated (Mounted on Pump)

Oil Cooler Strainer:

Model 150-D:

In-Line (Standard)

Panel Mounted (Optional)

Model Eclipse:

In-Line (Standard)

Operator Orientation:

(On-Site Operator Orientation and Training)

Contact Waterous Company for Availability

DS-4016 Page 1 of 3

The Following Items are Optional:

```
Hose and Fitting Kit:
(Provides Hoses and Fittings to connect Compressor, Sump, Balance Valve, Separator Filter and Oil Cooler)
     Model 150-D
       Without (Standard)
       With (Optional)
     Model Eclipse
       Not Used
Oil Inlet Check Valve:
(Required when Sump is installed 12 in. or more above Compressor Rotor centerline, retains oil in compressor)
     Model 150-D
       Without (Standard)
       With (Optional)
     Model Eclipse
       Not Used
Air Distribution Manifold:
(Provides connections for air supply to CAF discharges)
  Manifold:
     Model 150-D
       Without (Standard)
       Three Ports (Optional)
       Four Ports (Optional)
       Five Ports (Optional)
     Model Eclipse
       Five Ports (Included)
  Air Valves:
     Model 150-D
       Without (Standard)
       Electric (Optional)
       Manual (Optional)
     Model Eclipse:
       Electric (Included)
  Port Caps:
     (One each 12 JIC, 8 JIC and 6 JIC for capping un-used manifold parts)
        Without (Standard)
        With (Optional)
  Auxiliary Air Kit:
     (Provides fittings, hoses, air valve and panel connection)
        Without (Standard)
        1/4 in. NPT (F) Panel Connection (Optional)
        3/4 in. NPT (F) Panel Connection (Optional)
Air Pressure Gauge Kit:
     (Provides fittings, hoses and air gauge)
        Without (Standard)
        Dual Scale, PSI and Kpa (Optional)
```

Continued on next page

Single Scale, Mpa (Optional)

DS-4016 Page 2 of 3

Static Mixers (Scrubbers):

See CAFS Accessories Data Sheet DS-4025

CAFS Discharge Manifold:

See CAFS Accessories Data Sheet DS-4025

Victaulic Clamp:

See CAFS Accessories Data Sheet DS-4025

ICS Valves:

See Data Sheet DS-4026

Air Discharge Kits:

See Data Sheet DS-4027

Foam Pump:

See Data Sheet DS-4014

DS-4016 Page 3 of 3