



FOAM SYSTEMS

CAFSystems™

FIRE PUMPS

MODULAR SLIDE-IN

150-70-ECL

Our slide-in, modular compressed air foam system is designed and constructed to simultaneously discharge water, foam solution or compressed air foam. The system also features compressed air for pneumatic tools and can pump water or air independently.



BENEFITS OF COMPRESSED AIR FOAM

- 80% of water content in the foam is effectively used for fire fighting
- Improved firefighting safety
- Faster knockdown time
- Less property damage
- Less water used

PERFORMANCE

- 150 GPM @ 150 PSI
- 567 l/min @ 10 bar
- 70 SCFM @ 125 PSI
- 1.97 M³/min @ 8.6 bar

SPECIFICATIONS

- Kohler 49 HP (36.5 kW) diesel-fueled engine
- Waterous CPD-2 Pump
- Rand 70 CFM compressor
- Steel Frame
- AQUIS™ 1.5 Foam Proportioner
- Touch Screen Control

SPECIFICATIONS – SLIDE-IN CAFSYSTEM: 150-70-ECL

A Medium Sized Slide-In with Extra Large Performance

150-70-ECLPerformance							
	FLOW			PRESSURE			
	GPM	l/min	l/sec	PSI	bar	kPa	MPa
Water Performance	250	950	15.8	100	6.9	690	0.69
	150	567	9.45	150	10	1000	1.0
Air Performance	CFM	M ³ /Min		PSI	bar	kPa	MPa
	70	1.97		100	6.9	690	0.69
				125	8.6	860	0.86
SIMULTANEOUS FLOWS							
140 GPM and 70 CFM @ 125 PSI (532 l/min and 1.97 M ³ /Min @ 8.6 bar)							

CAFSystem Components

- Rand 70 CFM (2.8m³/min)
- Aquis™ 1.5 Foam Proportioner

Engine Specifications

- Kohler, Model KD12504TCR, four-cylinder, liquid-cooled, delivering a maximum of 49 HP (36.5 kW), four-cycle, diesel fueled. Three (3) year manufacturer's warranty.
- The engine uses a pulse fuel pump (fuel tank not supplied). Pressure/lube system with spin-on oil filter. An extension hose is installed on the engine oil drain located at the oil pan and a plug installed in the end of the hose to facilitate oil changes.
- 12 or 24-volt electric with 80A/12v or 40A/24v alternator, electric ignition and start switch panel.
- Spark Arrestor Muffler

Pump/Transmission Specifications

- Waterous CPD-2 Centrifugal water pump, aluminum case, double-hubbed bronze impeller, stainless steel shaft and maintenance-free mechanical seal.
- 3-inch NPT Intake
- 2-inch NPT Discharge
- Venturi Primer w/electric activation switch
- "Poly Chain" drive transmission with an automatic tensioner and 8mm pitch sprockets.

Tellurus Control Panel:

- One-button Control
 - Engine controls start/stop and throttle
 - Engages air compressor and foam proportioner
 - Select Wet or Dry Foam, Air or Water Only

Operator's Control Panel:

- Chrome-plated discharge connection
- Venturi priming system w/push to prime activation
- Auxiliary compressed air outlet and valve control
- LED Lighting
- I/C Push-Pull valve actuators

Frame:

High-strength, steel frame

Warranty

Waterous Seven-Year Limited Warranty

Conditions of Sales

For details on Waterous Conditions of Sales, refer to F-2190, *Conditions of Sales* located on the Waterous web site at www.waterousco.com or by contacting Waterous.

Air Compressor:

The air compressor is an oil-flooded, rotary screw type, sized to supply a minimum of 70 CFM (2.8 m³/min) of usable air.

Foamulators:

Equipped with two (2) 1.5" Foamulators using an independent, patented.

pressure regulation, which keeps constant mixing pressure in the mixing chamber of the FOAMULATOR. This pressure regulation allows a variation of pump discharge pressure above the minimum working pressure of the Gen 2.0 without disrupting the function of the system or changing the consistency of the extinguishing agent.

Air Compressor Oil System:

A spin-on, full-flow oil filter unit is part of the system to control oil flow to the cooler. All lines are routed in braided hose conforming to SAE 100R1 standards for hydraulic hose.

Modular Air/Oil Separator:

Replacement elements for the oil filter and separator are available.

Air Compressor Cooling System:

The air compressor is cooled by a shell and tube type cooler. The system maintains recommended operating temperatures throughout the full operational range in ambient temperatures up to 115°F (46.1° C).

Options:

- **On-Site Delivery Instruction** - Contact factory for pricing.
- **Threads on panel intake and discharges HN/NST, NPSH, BSP or STORZ**
- **1.5" discharge for front turret**
- **Top and Side Enclosures**

Air Lines:

All air lines are rated to a minimum of 250 psi (17.2 bar). Air-line fittings are constructed of brass, bronze or steel. Stainless steel or brass check valves are provided at all air injection points to prevent water back-flow into the air lines. All hoses shall be secured to the frame with insulating clamps and located away from any heat sources.

Plumbing:

Inlet:

Inlet piping is 3" with 2.5" tank to pump stainless steel pipe with 2.5" overboard connection direct tank fill, F-NST swivel. (no, overboard suction).

Discharge:

Plumbing to two panel mounted 1.5" discharge water/foam/CAFS outlets, and one panel mounted 1.5" water only outlet M-NST incorporate a stainless-steel manifold and welded stainless steel pipe. All discharge plumbing is designed and tested to a minimum of 500 psi (34.5 bar) burst pressure.

Drains:

Panel mounted drain valves are provided to drain water from the water pump, discharge manifold and compressor cooler.

Foam Proportioner:

- Aquis™ Foam Proportioner controlled by Waterous Tellurus digital control system, pump module with electric motor/motor driver and microcontroller unit, foam concentrate strainer, shielded electrical cables for connection of all electronic components, foam inject check valve, WYE Strainer and flowmeter and tee.